



## USB 2.0 16-in-1 **AE161** Internal Card Reader



>> Apacer USB 2.0 Internal Card Reader is designed to be part of the desktop PC with the advancement of multimedia and digital applications. Four-slot design supports all memory cards, and the reader functions as a multi-task transfer media between different types of memory card to meet a wide variety of usage.

**AE161 supports memory cards:** SD / MMC / MMCplus / CF / miniSD / microSD (adapter needed) / RS-MMC / MMCmobile / MS / MS Duo / MS PRO / MS PRO Duo / Microdrive / SM / xD



## ■ USB Interface

- Compatible with USB specification revision 2.0
- Backward compatible with existing USB 1.1 ports
- A true "plug & play" connection; supports hot swapping function
- Get power directly from USB port; no external power or batteries required.

## ■ Four slots integrated to support

- CompactFlash Card Type I/II, IBM Microdrive, Magicstor,
- SmartMedia Card, xD-Picture Card,
- MultiMedia Card, RS-MMC Card, Secure Digital Card, miniSD,
- Memory Stick Card, Memory Stick PRO Card, MagicGate (Access only), and Memory Stick Duo Card and Memory Stick PRO Duo Card.

## ■ Panel Color

Beige



Black



Silver



# Specifications

Interface	Compliant with USB 1.1 and 2.0	
LEDS	LED on: Flash Card is inserted	LED blink: Data is accessed
Socket	Slot 1	CF I, CF II, Microdrive, Magicstor
	Slot 2	Secure Digital Card, miniSD, microSD(adapter), MultiMedia Card, RS-MMC, MMCplus, MMCmobile, MMCmicro(adapter)
	Slot 3	Memory Stick, MS PRO, MS Duo, MS PRO Duo, MagicGate
	Slot 4	SmartMedia Card, xD-Picture Card
Transfer rate	Max. up to 480 Mbps	
Case	Metal	
Supported Flash Cards	CompactFlash: 4MB or higher Microdrive: 340MB or higher Magicstor: 2.2GB SmartMedia Card: up to 128MB xD-Picture Card: up to 1GB MultiMedia Card: 8MB or higher RS-MMC Card: 64MB or higher MMCplus Card: 128MB or higher MMCmobile Card: 128MB or higher MMCmicro Card(adapter): 128MB or higher Secure Digital Card: 8MB or higher miniSD Card: 16MB or higher microSD Card(adapter): 128MB or higher Memory Stick: 4MB or higher MS Duo: 8MB or higher MS PRO: 128MB or higher MS PRO Duo: 128MB or higher MagicGate: 128MB or higher	
Power	100mA(without flash cards)from the motherboard USB connector	
Operating System Support	Win 98/98 SE(driver), 2000, ME, XP, Mac OS 9.(driver) or above, Linux OS 2.4 or above	
Dimensions	101.6 X 92 X25.4mm	
Unit Weight	150g	

## Global Presence

### ■ Taiwan (Headquarters)

Apacer Technology Inc.  
TEL: +886-2-2696-1666  
FAX: +886-2-2696-1668

### ■ Japan

アパサーテクノロジーズ株式会社  
Tel: +81-3-5817-3498  
Fax: +81-3-5817-3497

### ■ China

Apacer Electronic(Shanghai) Co., Ltd  
Tel: +86-21-5206-6933  
Fax: +86-21-5206-6939

### ■ Europe

Apacer Technology B.V.  
Tel: +31-73-645-9670  
Fax: +31-73-645-9629

### ■ U.S.A.

Apacer Memory America, Inc.  
Tel: +1-408-232-1291  
Fax: +1-408-432-6025

**Apacer**  
Access the best